



HIPPO STOP is the Mini magnetic sludge remover filter, with connector shanks and drain tap. Designed for simple and quick installation in limited space (less than 4 cm inter-axis and 8 cm as maximum height) under the boilers.

- ✓ 500 micron cartridge
- ✓ Neodymium magnets 11.000 Gauss
- ✓ Boilers up to 35 kW

Thanks to its patented design the flow of water will be always inside of the filtering cartridge, touching the magnetic bar as first treatment step.

The filter is very compact in size but suitable to multi-treatment purposes: settling and filtering the dirt, capturing the iron oxides. It is equipped with an internal chamber to isolate the magnetic bar, and a brand new integrated valve to stop the inlet water.

| CODE | MODEL | MATERIALS | | | FLOW RATE ($\Delta P=0,2BAR$) Lt/min | PN BAR | CONNECTIONS | SIZE in mm | | FILTERING CAPACITY MICRON | MAX. WATER TEMP. °C | PIECES x pack. |
|----------|------------------|-----------|----------|-----------|--|-----------|-------------|---------------|-----|---------------------------------|---------------------------|-------------------|
| | | HEAD | BOWL | CARTRIDGE | | | | A | B | | | |
| HIPPOWHS | HIPPO STOP WHITE | TERMOPL. | TERMOPL. | INOX | 25 | 7 | ¾" MF | 90 | 100 | 500 | 90 | 24 |
| HIPPOBLS | HIPPO STOP BLACK | TERMOPL. | TERMOPL. | INOX | 25 | 7 | ¾" MF | 90 | 100 | 500 | 90 | 24 |

