



Product Identification

600251

- OLI80 Mechanic Simflex

Definition and Application

- Preassembled structure for setting in masonry walls, to installation of wall-hung sanitary appliances.

Technical Features

Structure

- Metal, galvanized, corrosion resistant

Cistern

- Dual flush of 6/3 in-wall cistern compatible with either dual or single flush actuators
- Adjustable flush volumes
- 80mm thickness
- Mechanic actuation
- Working pressure from 0,1 to 16 bar
- Resistance to atmospheric humidity (Hr <90%).
- Polypropylene (PP) cistern highly resistant and inalterable to thermal stress
- Other versions compliant with: DIN/BELGAQUA standards
- EN 14055 marking CL1
- Silent Valve Class 1 NF certified
- Supplied with anti-condensation lining

Accessories

- 1 Flush pipe \varnothing 90 x 360
- 1 Seal for flush pipe \varnothing 125
- 1 Connecting pipe \varnothing 45 x 180
- 1 Pan rubber seal \varnothing 45
- 1 Protective box
- 1 G ½" stop valve
- 1 Protection sponge for the stop valve
- 1 Flush pipe \varnothing 56 x 165
- 1 Outlet bend \varnothing 90 / 90 L230
- 1 Adaptor \varnothing 90/110
- 1 Protection pipe \varnothing 90
- 1 Protection pipe \varnothing 45

Fixing accessories for wall structure:

- 4 Galvanized screws M8x60
- 4 Galvanized washers M8 DIN 9021
- 4 Bushing M8 for metal structure

For fixing hung wc on the structure:

- 2 Threaded rods M12
- 2 Protection for threaded rod
- 2 Protection cover
- 2 Toilet centring washer
- 2 Nuts M12
- 2 Washers \varnothing 34

Warranty

- Ten (10) years warranty according to the general selling terms, starting from the purchase date of the product.
- If the product is not correctly installed the warranty is not valid

Observations

- There are available similar products. For more information please consult our Sanitary Installation Systems catalogue or our site www.oli-world.com