

- Alliage Anti-Corrosion Doré
- Redémarrage Automatique
- Affichage LED
- Flux d'Air Puissant



CLIMATE TYPE **T3**

INVERTER

TROPICAL
Température extérieure 56°C

CLIMATISEUR ARMOIRE



économie
d'énergie



Filtre multi-
fonctions



Froid rapide



Chauffage
rapide



Mode Silence




Ecran LED



CONFORT

Refroidissement et chauffage rapides : l'armoire adapte la position des déflecteurs en fonction des modes de fonctionnement pour obtenir un



PERFORMANCE

l'armoire est en mesure de couvrir de grandes surfaces grâce au flux d'air puissant capable d'atteindre des zones jusqu'à une distance de 20 mètres .



Model Reference			WAIT-60.LH
Control type			Remote Controller
Nominal capacity		Btu/h	60 000
Cooling capacity		W	16706
Heating capacity		W	16706
EER for cooling		Btu/h~W - W/W	10,92 - 3,2
COP for heating		W/W	3,15
Moisture removal		Liters/h	5,5
Pressure	High(DP) - Low(SP)	MPa	4,5 - 1,9
Indoor noise level at cooling	Quite	dB(A)	47
Outdoor noise level		dB(A)	66
Climate type			T3
Power supply			230V~1 Phase/ 60Hz - 50Hz
Voltage Range		V	198~264
Current	Cooling - Heating	A	23,2 - 23,5
Power input	Cooling - Heating	W	5221 - 5303
MAX Current	Cooling - Heating	A	30 -30
MAX Power input	Cooling - Heating	W	5700 - 6200
Refrigerant		kg	R410A/4.25
Compressor	Model		GTH420SKPC8DQ
Fan System			
Indoor air volume(Cooling/Heating)		m³/h	2100/2300
Indoor fan type			Centrifugal
Indoor fan motor		model	22001-000204 DC
Outdoor fan motor		model	25001-000392 DC
Connections			
Connecting Pipe	Gas	Inches	Φ19(3/4")
	Liquid	Inches	Φ9.52(3/8")
Others			
Net dimensions (W x D x H)	Indoor	mm	600×390×1918
	Outdoor	mm	1021×409×1339
Net weight	Indoor	kg	59
	Outdoor	kg	91
Packing dimensions (W x D x H)	Indoor	mm	2083×743×521
	Outdoor (without piping)	mm	1080×440×1480
	Outdoor (with piping)	mm	/
	Indoor	kg	69
Gross weight	Outdoor (without piping)	kg	104
	Outdoor (with piping)	kg	108