

INVERTER

TROPICAL
Température extérieure 56°C



CLIMATE TYPE **T3**

WAIT-48.LH

CLIMATISEUR TYPE ARMOIRE





			WAIT-48.LH
PERFORMANCES			
T1 Cooling capacity		(Btu)	48000
		(W)	14068
		(frig/h)	12000
T3 Cooling capacity		(Btu)	40800
		(W)	11958
		(frig/h)	10200
T1 Heating capacity		(Btu)	49000
		(W)	14361
		(frig/h)	12250
T1 Cooling mini/maxi		(W)	4220~14400
		(Btu)	15500~52866
T3 Cooling mini/maxi		(W)	4220~14400
		(Btu)	15500~52866
T1 Heating mini/maxi		(W)	4220~14400
		(Btu)	15500~52866
Input power cooling		(W)	4263
Input power heating		(W)	3968
Running current cooling		(A)	20.2
Running current heating		(A)	18.8
Moisture removal		(l/h)	3
Air flow	high	(m³/h)	1550
	medium	(m³/h)	1280
	low	(m³/h)	1180
Remote control			YES
Inverter			YES
Gas refrigerant			R410a
Charge		(g)	2500
E.E.R.		(W/W)	3.3
E.E.R. T3		(Btu/W)	8.5
Voltage		IDU (V-Ph)	220-240 V - 1 PH
		ODU (V-Ph)	220-240 V - 1 PH
Frequency		(Hz)	50 Hz
FEATURES			
Indoor unit			
Net dimensions	height	(mm)	1775
	width	(mm)	540
	depth	(mm)	415
Gross dimensions	height	(mm)	1893
	width	(mm)	632
	depth	(mm)	535
Net weight		(kg)	54
Gross weight		(kg)	64
Sound pressure	high	(dB(A))	51
	medium	(dB(A))	48
	low	(dB(A))	45
Excessive operating pressure			
	discharge	(MPa)	4.5
	suction	(MPa)	1.9
AEC			
Max current		(A)	25
Max power input		(W)	5000
Outdoor unit			
Net dimensions	height	(mm)	1089
	width	(mm)	494
	depth	(mm)	858
Net weight		(kg)	73
Air flow		(m³/h)	5000
Noise level		(dB(A))	63
Excessive operating pressure			
	discharge	(MPa)	4.5
	suction	(MPa)	1.9
Climate suitability			T3
Max current		(A)	25
Max power input		(W)	5000
Compressor type			ROTARY
Connection pipe	mini length allowed	(m)	3
	maxi length allowed	(m)	20
	maxi height allowed	(m)	15
	diameter liquid	(mm) (inch)	9.52 - 3/8
	gas connexion	(mm) (inch)	15.88 - 5/8
OPTIONS			
LED display			YES
Timer		(h)	YES
I FEEL Function*			YES
This function maintains the set temperature where the remote controller is located			