

WKIT-6024.LH

CLIMATISEUR CASSETTE




TROPICAL
Température extérieure 50°C





Reference		WKIT-6024.LH
PERFORMANCES		
Cooling capacity	(Btu)	55000
	(W)	16120
	(frig/h)	13750
Heating capacity	(Btu)	58000
	(W)	17000
	(frig/h)	14500
Cooling mini/maxi	(W)	5600~16800
	(Btu)	19100~57300
Heating mini/maxi	(W)	5950~18700
	(Btu)	20300~63800
Input power cooling	(W)	5370
Input power heating	(W)	5310
Running current cooling	(A)	8,2
Running current heating	(A)	8,1
Air flow	high - (m3/h)	2000
	medium - (m3/h)	1700
	low - (m3/h)	1500
Remote control		Yes
Inverter		Yes
Gas refrigerant		R410a
Charge	(g)	2800
E.E.R.	(W/W)	3,00
C.O.P.	(W/W)	3,20
Voltage	(IDU V-Ph)	220-240 V - 1 PH
	(ODU V-Ph)	380-415 V - 3 PH
Frequency	(Hz)	50 Hz
FEATURES		
Indoor unit		
Net dimensions	height - (mm)	290
	width - (mm)	840
	depth - (mm)	840
Net weight	(kg)	30,0
Sound pressure	high - (dBA)	51
	medium - (dBA)	48
	low - (dBA)	45
Outdoor unit		
Net dimensions	height - (mm)	1010
	width - (mm)	850
	depth - (mm)	410
Net weight	(kg)	75
Noise level	(dBA)	58
Excessive operating pressure	discharge - (MPa)	4,5
	suction - (MPa)	1,9
Max current	(A)	10
Max power input	(W)	6400
Compressor type		ROTARY
Connection pipe	maxi length allowed - (m)	50
	maxi height allowed - (m)	30
	diameter liquid - (mm inch)	9.52(3/8")
	gas connexion - (mm inch)	15.88(5/8")
OPTIONS		
LED display		Yes
Timer	(h)	24
I FEEL Function* This function maintains the set temperature where the remote controller is located		Yes