

WKIT-6024.LH

CLIMATISEUR CASSETTE



TROPICAL
Température extérieure 50°C





Reference		WKIT-6024.LH
PERFORMANCES		
Cooling capacity	(Btu) (W) (frig/h)	55000 16120 13750
Heating capacity	(Btu) (W) (frig/h)	58000 17000 14500
Cooling mini/maxi	(W) (Btu)	5600~16800 19100~57300
Heating mini/maxi	(W) (Btu)	5950~18700 20300~63800
Input power cooling	(W)	5370
Input power heating	(W)	5310
Running current cooling	(A)	8,2
Running current heating	(A)	8,1
Air flow	high - (m3/h) medium - (m3/h) low - (m3/h)	2000 1700 1500
Remote control		Yes
Inverter		Yes
Gas refrigerant		R410a
Charge	(g)	2800
E.E.R.	(W/W)	3,00
C.O.P.	(W/W)	3,20
Voltage	(IDU V-Ph) (ODU V-Ph)	220-240 V - 1 PH 380-415 V - 3 PH
Frequency	(Hz)	50 Hz
FEATURES		
Indoor unit		
Net dimensions	height - (mm) width - (mm) depth - (mm)	290 840 840
Net weight	(kg)	30,0
Sound pressure	high - (dBA) medium - (dBA) low - (dBA)	51 48 45
Outdoor unit		
Net dimensions	height - (mm) width - (mm) depth - (mm)	1010 850 410
Net weight	(kg)	75
Noise level	(dBA)	58
Excessive operating pressure	discharge - (MPa) suction - (MPa)	4,5 1,9
Max current	(A)	10
Max power input	(W)	6400
Compressor type		ROTARY
Connection pipe	maxi length allowed - (m) maxi height allowed - (m) diameter liquid - (mm inch) gas connexion - (mm inch)	50 30 9.52(3/8") 15.88(5/8")
OPTIONS		
LED display		Yes
Timer	(h)	24
I FEEL Function* This function maintains the set temperature where the remote controller is located		Yes